COMMERCIAL BUILDING STANDARD SPECIFICATIONS

STRUCTURAL/EXTERIOR

401 B LOAD ROOF TRUSSES AT 24" OC

5/12 ROOF PITCH

5/8" O.S.B. ROOF SHEATHING

OWENS CORNING ARCHITECTURAL SHINGLES w/15LB ROOF

UNDERLAYMENT FELT PAPER

R-30 KRAFT FIBERGLASS INSULATION

2"x 6" EXTERIOR WALLS AT 16" OC

MASTIC VINYL SIDING

APPLIED OVER 7/16" O.S.B.

R-21 FIBERGLASS INSULATION

DOUBLE 6 ALUMINUM PERFORATED SOFFIT AND AIR VENT RIDGE VENT 20

VINYL DOUBLE HUNG WINDOWS w/ INSULATED LOW "E" GLASS

1 3/4" THERMATRU INSULATED EXTERIOR FIBERGLASS 36" DOORS

8'0" CEILING HEIGHT

FLOOR SYSTEM

FLOORS SIZED PER LOADS FOR DESIGNATED USE 28' WIDE: 2"x 10" JOISTS AT 16" OC SYP MSR2400 3/4" O.S.B. TONGUE AND GROOVE SUBFLOOR, GLUED AND

CUSHIONED VINYL FLOORING INCLUDING 1/4" UNDERLAYMENT IN APPLICABLE AREAS

COMMERCIAL GRADE CARPET

INTERIOR

DOUBLE MARRIAGE WALL 2"x 4" AT 16" OC INTERIOR WALLS, 2"x 4" AT 16" OC INTERIOR WALLS, 1/2" DRYWALL (PER CODE) VAPOR BARRIER PRIMER WHITE

WIRE CLOSET SHELF SYSTEM

KITCHEN/BATH

HANDICAP WATER CLOSET AND LAVATORY IN WHITE MIRROR AND LIGHTS AS SHOWN ON PLANS ANTI-SCALD FAUCETS EXHAUST FAN AND LIGHT

ELECTRICAL

40 CIRCUIT, 200 AMP PANEL BOX, IBC

ELECTRICAL WIRING AS PER NEC

ALL CIRCUITS WIRED INTO THE PANEL BOX w/ AMP

CONNECTORS INSTALLED TO MAKE CONNECTIONS

BETWEEN MODULES

ONE EXTERIOR GFCI RECEPTACLE PER EXTERIOR DOOR

PLUMBING

ALL PLUMBING STUBBED THROUGH FLOOR
VENT STUBBED INTO ATTIC AND FINISHED ON-SITE
EXTRA VENT FOR FUTURE USE
PEX OR COPPER WATER SUPPLY LINES STUBBED
PVC DRAIN, WASTE, VENT SYSTEM
SHUTOFF VALVES AT SINKS AND WATER CLOSETS

LAVATORIES

ADA COMPLIANT LAVATORY FAUCETS 18", 36", 42" GRAB BARS (AS REQUIRED) ADA COMPLAINT TOILETS EXHAUST FAN & LIGHT

HEATING

BOOTS AND REGISTERS OR HOT WATER
BASEBOARD STUBBED. ELECTRIC BASEBOARD ALSO AVAILABLE

BUILDER/DEALER RESPONSIBILITIES INCLUDE

(BUT ARE NOT LIMITED TO):

EXCAVATION, FOUNDATION, ADDITIONAL FASTENERS, INSTALLATION
OF SHIP-LOOSE MATERIALS, AND INTERIOR FINISH AT MARRIAGE
WALLS, UTILITY HOOK-UPS, AND CONNECTIONS.

10 YEAR LIMITED STRUCTURAL WARRANTY INFORMATION CONTAINED ON THIS PAGE IS SUBJECT TO CHANGE WITHOUT NOTICE.