

Specifications

| | |
|--------------------------|---|
| Applications | Residential Recessed Lighting |
| Average Life (Hrs) | 50,000 |
| Beam Angle | Flood |
| Beam Spread | 160 |
| Brand | ProLED |
| CRI | 90 |
| Color Temperature | 3000 |
| DesignLights Consortium | No |
| Dimmable | Yes |
| ENERGY STAR | Yes |
| Equivalent Wattage | 65 |
| Finish | White |
| HTS code | 9405406000 |
| Initial Lumens | 550 |
| Inner Carton Quantity | 1 |
| Input Current (Amps) | 80 |
| Input Frequency (Hz) | 50/60 |
| Lens | PC |
| Markets | Residential, Light Commercial |
| Master Carton Quantity | 24 |
| Maximum Overall Diameter | 4.72 |
| Maximum Overall Length | 0.413 |
| Prod Code | DLS4FR9/RD/930/LED |
| Product Category | LED FIXTURES |
| Product Description | 4 Round Slim Downlight 9W 3000K Dimmable Wet Location |
| Product Number | 89061 |
| TITLE20 Y/N | Y |
| Voltage (V) | 120 |
| Warranty (Yrs) | 5 |
| Wattage (W) | 9 |
| XREF Informational Video | /9W-RD IES.ies |



DLS4FR9/RD/930/LED 89061 4in Round Slim Downlight 9W 3000K Dimmable Wet Location

Product Number: 89061
UPC: 807154890613

